

Globe Wall 12

Globe Wall ist die feine Wandleuchte. Elegant im Design, schafft sie eine optisch entblendete Lichtverteilung nach oben und unten. Gefertigt in feinstem Aluminium, bringt sie hochwertige Stimmung in Bäder, Treppenhäuser, Flure und Wohnräume.

Mit Globe Wall werden Räume zu eleganten Wohlfühlorten. Die zwei entblendeten optischen Linsen der flachen Wandleuchte werfen sanftes Licht nach oben und unten an die Wand, was eine stimmungsvolle Atmosphäre schafft.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben

Farben	Artikelnummer
● Polished	FC20-0
● Sand White	FC20-5
● White	FC20-2
● Black	FC20-1

Dimensionen

Head
5 cm × 21,5 cm × 12 cm



Linse
Ø 12 cm

Body

Maße Verpackung (L x B x H)	29cm x 46cm x 30cm
Material	Aluminium
Oberfläche	Poliert
Gewicht	1,5kg
Gewicht inkl. Verpackung	2,5kg
Montageart	Wandaufbau
Nennspannung	220–240V
Leistungsaufnahme	12W
Leuchteneffizienz	62lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	FC20-0

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	747lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	50% direkt / 50% indirekt
Lichtverteilung	Symmetrisch
Farbtemperatur	2700K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt

Globe Wall 12

Globe Wall is the fine wall light. Elegant in design, it creates an optically glare-free light distribution upwards and downwards. Made of the finest aluminum, it creates a high-quality atmosphere in bathrooms, stairwells, corridors and living rooms.

With Globe Wall, rooms become elegant places of well-being. Mount its minimalist shape at eye level and enjoy the fine light distribution of its two optical lenses, which shine the light upwards and downwards onto the wall.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
Polished	FC20-0
Sand White	FC20-5
White	FC20-2
Black	FC20-1

Dimensions

Head
5 cm × 21,5 cm × 12 cm



Lense
Ø 12 cm

Body	Packaging dimensions (L x W x H)	29cm x 46cm x 30cm
	Material	Aluminum
	Surface	Polished
	Weight	1,5kg
	Weight incl. packaging	2,5kg
	Mounting type	Wall-mounted (surface)
	Rated voltage	220–240V
	Power consumption	12W
	Luminaire efficiency	62lm/W
	Connection cable (number of cores)	3
	Protection class	I
	SKU	FC20-0
Light	Light source	LED
	Luminous flux	747lm
	Color rendering index	CRI >90
	Light emission	50% direct / 50% indirect
	Light distribution	Symmetric
	Color temperature	2700K
	Light color	Warm White
	Dimmable	Yes
	Type of dimming	Trailing edge