

GRAU

Niceone Chandelier Six

Niceone Chandelier Six ist der minimale Lüster. Über dem Tisch oder frei im Raum, verzaubert er den Raum. Preisgekröntes Design, feinste Finishes und brillante Lichtstimmung – made in Germany.

Die optische Linse lenkt das Licht blendfrei und lichtstark 360° nach außen. Dimme das Licht per GRAU App und konfiguriere Lichtszenen.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben	Farben	Artikelnummer
	White/White	CNO06-3
	Raw/Charcoal	CNO06-8
	Black/Black	CNO06-1
	Polished/Grey	CNO06-0

Dimensionen



Body

Pendellänge	2m
Maße Verpackung (L x B x H)	83cm x 43cm x 9cm
Material	Aluminium
Oberfläche	Pulverbeschichtet
Gewicht	7,5kg
Gewicht inkl. Verpackung	18kg
Montageart	Deckenaufbau
Nennspannung	220–240V
Leistungsaufnahme	6x11W
Leuchteneffizienz	56lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	CNO06-3

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	6 x 620lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	Direkt
Abstrahlwinkel	54°
Lichtverteilung	Symmetrisch
Farbtemperatur	2700–2200K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt
Warm Dim	Ja
GRAU App Upgrades möglich	Ja
Umbau auf DALI möglich	Ja

GRAU

Niceone Chandelier Six

Niceone Chandelier Six is the minimalist chandelier. Above the table or free-standing in the room, it enchants the room. Award-winning design, the finest finishes and brilliant mood lighting – made in Germany.

The optical lens directs the light glare-free and brightly 360° outwards. Dim the light via the GRAU app and configure light scenes.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
White/White	CNO06-3
Raw/Charcoal	CNO06-8
Black/Black	CNO06-1
Polished/Grey	CNO06-0

Dimensions



Body

Pendant length	2m
Packaging dimensions (L x W x H)	83cm x 43cm x 9cm
Material	Aluminum
Surface	Powder-coated
Weight	7,5kg
Weight incl. packaging	18kg
Mounting type	Ceiling-mounted (surface)
Rated voltage	220–240V
Power consumption	6x11W
Luminaire efficiency	56lm/W
Connection cable (number of cores)	3
Protection class	I
SKU	CNO06-3

Light

Light source	LED
Luminous flux	6 x 620lm
Color rendering index	CRI >90
Light emission	Direct
Beam angle	54°
Light distribution	Symmetric
Color temperature	2700–2200K
Light color	Warm White
Dimmable	Yes
Type of dimming	Trailing edge
Warm Dim	Yes
GRAU App upgrades possible	Yes
Conversion to DALI possible	Yes