

Niceone Trace

Niceone Trace ist die minimale Pendelleuchte für den Tisch. Die optische Linse lenkt das Licht blendfrei und lichtstark 360° auf den Tisch. Preisgekröntes Design, feinste Finishes und brillante Lichtstimmung – made in Germany.

Warm Dim passt die Lichtfarbe automatisch beim Dimmen an. Dimme das Licht per GRAU App und konfiguriere Lichtszenen.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben

Farben	Artikelnummer
Black/Black	CNO13-1
Raw/Charcoal	CNO13-8
White/White	CNO13-3
Polished/Grey	CNO13-0

Dimensionen



Body

Pendellänge	2m
Maße Verpackung (L x B x H)	134cm x 21cm x 20cm
Material	Aluminium
Oberfläche	Pulverbeschichtet
Gewicht	4kg
Gewicht inkl. Verpackung	6kg
Montageart	Deckenaufbau
Nennspannung	220–240V
Leistungsaufnahme	3x11W
Leuchteneffizienz	56lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	CNO13-1

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	3x 620lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	Direkt
Abstrahlwinkel	54°
Lichtverteilung	Symmetrisch
Farbtemperatur	2700–2200K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt
Warm Dim	Ja
GRAU App Upgrades möglich	Ja
Umbau auf DALI möglich	Ja

Niceone Trace

Niceone Trace is the minimal pendant luminaire for the table. The optical lens directs the light glare-free and bright 360° onto the table. Award-winning design, the finest finishes and brilliant mood lighting – made in Germany.

Warm Dim automatically adjusts the light color when dimming. Dim the light via the GRAU app and configure light scenes.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
Black/Black	CNO13-1
Raw/Charcoal	CNO13-8
White/White	CNO13-3
Polished/Grey	CNO13-0

Dimensions



Body

Pendant length	2m
Packaging dimensions (L x W x H)	134cm x 21cm x 20cm
Material	Aluminum
Surface	Powder-coated
Weight	4kg
Weight incl. packaging	6kg
Mounting type	Ceiling-mounted (surface)
Rated voltage	220–240V
Power consumption	3x11W
Luminaire efficiency	56lm/W
Connection cable (number of cores)	3
Protection class	I
SKU	CNO13-1

Light

Light source	LED
Luminous flux	3x 620lm
Color rendering index	CRI >90
Light emission	Direct
Beam angle	54°
Light distribution	Symmetric
Color temperature	2700–2200K
Light color	Warm White
Dimmable	Yes
Type of dimming	Trailing edge
Warm Dim	Yes
GRAU App upgrades possible	Yes
Conversion to DALI possible	Yes